



Field System Topics

Ed Himwich, John Gipson,
and Jonathan Quick

FS Linux 7

- ◆ FS Linux 7 Distribution now available
 - ⊕ Based on Debian “etch”
 - ⊕ Uses RAID1 for more robust operations with two disks
 - ⊕ Back-up scheme with three disks rotates disks periodically
 - ⊕ Upgrade path from earlier systems is:
 - Clean install
 - Copy /usr2 partition, etc. to new system
 - ⊕ Install and upgrade thoroughly documented
 - `/usr2/fs/misc/FSL7_*`
 - `atri.gsfc.nasa.gov:/docs/FSL7_*`
 - ⊕ GPIB support
 - Open source driver does not support older devices
 - NI GPIB-RS232 device
- ◆ FS Linux 8, based on “EtchAndahalf” (?) in the future
- ◆ Older systems should use a Router/Firewall
 - ⊕ Inexpensive, <US\$100
- ◆ Old hard disks (> 5 years) should be replaced

Current Status - FS 9.10.3

- ◆ Mark 5A & 5B Recorder Support
- ◆ Mark 5 Sampler Module Support
 - ⊕ Rack types Mark5 and VLBA5
- ◆ GNPLT bug fixes
- ◆ Systests improved and Mark5B rack/recorder support
- ◆ DRUDG
 - ⊕ Support for Dymo printers under FS Linux 5
“woody”, 6 “sarge”, 7 “etch”
- ◆ TNX command expanded
 - ⊕ Supports multiple forms of error messages

FS 9.10.4 (September 2008)

- ◆ Some small maintenance fixes
- ◆ Rewritten *logpl* plotting utility
 - ⊕ Python based
 - ⊕ XY plots
- ◆ Routine sampling of PCal for geodesy experiments
- ◆ Updated *plotlog* plotting utility
 - ⊕ Pcal amps normalized by Tsys
 - PCal amp plots
 - Pcal phase versus amp plots
 - ⊕ Select plots to include/exclude by regular expressions

FS 9.11.0 (October 2008)

- ◆ Automatic/Continuous PCal extraction with Mark IV Decoder
 - ⊕ Extracts all tones from all recorded channels
 - ⊕ Global control from *drudg* skedf.ctl control file
 - Able to use VEX specified extraction
 - Flagging for Cal and TPZERO
 - ⊕ Further expansion of *plotlog*
 - Multiple tones per channel
 - Fit sinusoids for frequency one and two in 2π phase
 - ⊕ AIPS format file generated from post-processing
 - ⊕ Can be expanded for Mark 5B
- ◆ Slow disk warning
- ◆ LO_CONFIG Command
- ◆ VEX extension for VLBA
- ◆ Let me know if you need new features or bug fixes

FS 9.11.1 (December 2008)

- ◆ DBBC/DBE support
 - ⊕ Client/server model?
- ◆ Multiple Mark 5 recorders
- ◆ Other possibilities:
 - ⊕ New *gnplt*
 - ⊕ CHEKR monitoring of Mark5
 - ⊕ Update Mark 5 “Remaining Capacity” display while recording
- ◆ 80 Hz Radiometry

Longer term development items I

- ◆ Client/server model for remote operations
- ◆ Documentation Update, wiki for documentation, operations discussion, bug reports
- ◆ Improve prediction of disk pack change times
- ◆ Pointing software clean-up
 - ⊕ Eliminate redundancies in pointing configuration information by introducing a source coordinate database file and reorganizing point.prc and ctlpo.ctl (*aquir* control file).
 - ⊕ Documentation clean-up to reflect new procedures and utilities
- ◆ Improved Tsys
 - ⊕ Most items completed
 - ⊕ Post processing program to generate AIPS (ANTAB) format TSYS files from Cormac Reynolds
 - ⊕ Periodic firing of calibration diode with flagging needed
- ◆ Convert from fort77/f2c to gFORTRAN
 - ⊕ Will allow use of source level debugger
 - ⊕ Must maintain compatibility with f2c for older distributions

Longer term development items II

- ◆ Band changes
 - ⊕ Band configuration procedures added to set-up by DRUDG.
 - The DRUDG control file will be expanded to include a table of station defined procedures that can be used to set-up local station equipment for a band. These procedures can also be used manually by the operator as needed. Note that use of the existing SAVE_FILE command can be used in these procedures and INITI to recover the receiver set-up between FS terminations and restarts.
 - ⊕ CALON and CALOFF SNAP variables.
 - This intended to deal with stations that have different cal control methods for different bands. The idea is that variables will be introduced into SNAP, specifically two: CALON and CALOFF. These can be defined by the band set-up procedures described above and used as \$CALON and \$CALOFF in procedures when the noise diode needs to be controlled.

Additional Future Items

- ◆ IF patching automation for Mark IV racks
 - ⊕ EVN has hardware design, but not implemented in field yet. We will need one relatively simple SNAP command to support it:
 - A special version of PATCH and a way to control which version is used.
- ◆ Mark IV decoder support
 - ⊕ This is beyond the phase-cal monitoring mentioned above, mainly a few SNAP commands to control the decoder manually. Most of the effort here is actually divining what is needed and developing documentation

FS Priority List

- ◆ Separate LCP/RCP RX temperature in .rxg files
- ◆ LO_CONFIG command
- ◆ Slow disk warning
- ◆ 80 Hz Radiometry
- ◆ Periodic monitoring (*chekr*) of Mark 5
- ◆ DBBC support
- ◆ Update Monit/Expanded Status Reporting/*erchk*
- ◆ GNPLT Update
- ◆ ...